

# Vital Signs Monitors



**NT2A**  
◆ SpO2 / PR



**NT2C**  
◆ SpO2/NIBP/TEMP

- Bright, Easy-to-Read Large LED Display
- Durable, Compact and Lightweight
- Long-life Internal Rechargeable Battery for Uninterrupted Monitoring
- Audible/Visual Three Level Alarms with Alarm Volume Control
- 72-hour Data Memory Allowing On-screen Viewing of SpO2 and Pulse Rate Trends
- Suitable for Adult, Pediatric and Neonate

### Performance Measurement Range:

SpO<sub>2</sub>: 0%~100%  
Pulse Rate: 30bpm~250bpm

### SpO<sub>2</sub> Accuracy:

Adults, Pediatrics: 70%~100% ±2%  
0%~69% unspecified  
Neonates: 70%~100% ±3%  
0%~69% unspecified

### Pulse Rate Accuracy:

Adults, Pediatrics, Neonates: ±3%

### Non-Invasive Blood Pressure:

Measurement type: Adult, Pediatric, Neonatal  
Measurement range:

Adult:	Systolic	40 ~ 270mmHg
	Diastolic	20 ~ 200mmHg
	Mean	30 ~ 220mmHg
Pediatric:	Systolic	40 ~ 180mmHg
	Diastolic	15 ~ 160mmHg
	Mean	20 ~ 170mmHg
Neonatal:	Systolic	30 ~ 140mmHg
	Diastolic	15 ~ 100mmHg
	Mean	20 ~ 115mmHg

Accuracy: Meets ANSI/AAMI SP10-1992

Resolution: 1mmHg

Protection: over pressure

### Alarm:

Audible/Visual Alarms  
Adjustable Alarm Limits

### Temperature:

Measurement range: 25 ~ 45 °C  
Accuracy: ± 0.2 °C

### Output:

RS-232 Serial Port for Digital Output  
Nurse Call Function

### Available Optional Accessories:



Adult Finger Sensor



Pediatric Finger Sensor



Neonatal Y-Type



NIBP Cuffs



TEMP Sensor

### Electrical Instrument:

Power Requirements: 100~240VAC, 50/60Hz, 40VA  
Fuse Rating: 1.0A

### Battery:

Internal Battery: 12V  
Battery Capacity: ≥ 24 hours

### Environment:

Operating:  
Temperature: 5°C~40°C (41°F~104°F)  
Humidity: 10%~95%  
Transport/Storage:  
Temperature: -20°C~70°C (-4°F~158°F)  
Humidity: 10%~95%

### Physical Characteristics:

Dimensions: 264mm(W) x 95mm(H) x 172mm(D)  
10.39in(W) x 3.74in(H) x 6.77in(D)  
Net Weight: 2.25kg/5 lb

### Compliance:

1. SpO<sub>2</sub>: ISO 9919: 2005(E)
2. Safety Standards:  
EN 60601-1: 1990+A1: 1993+A2: 1995+A13: 1996
3. Alarm: IEC60601-1-8: 2005
4. EMC: EN 60601-1-2: 2007, Group 1 Class A
5. Environment : WEEE (2002/96/EC)

## NEWTECH, INC.

No. 1 Chuangye Building, Unit C  
6th Industrial Rd., Nanshan District  
Shenzhen, Guangdong 518067  
CHINA

Tel: +86-755-26525848

Fax: +86-755-26520737

www.sznewtech.com

E-mail: intl-sales@sznewtech.com

200901-vital-V1.2

### Distributor



**SUBJECT TO CHANGE WITHOUT NOTICE**